



Wald

EZKA/2018-05/00002-3

Met vaste brandstof gestookte ruimteverwarming
Roomheater fired by solid fuel capable of intermittent operation
Espace chauffé avec un combustible solides
Kaminofen für feste Brennstoffe

Afstand tot brandbare materialen; zij-, achterkant Distance to adjacent combustible materials; side, back Espace depuis les matériaux inflammables; côté, arrière Abstand bis brennbarer Materialien; seite, hinter	80 cm, 15 cm (min)
--	--------------------

ECO Design emissie in verbrand product Emission ECO Design in combustion products ECO Design émission dans les produits de combustion ECO Design Emission in verbranntes Produkt	CO ≤ 1500 mg/m ³ PM ≤ 40 mg/m ³ OGC ≤ 120 mg/m ³ NOx ≤ 200 mg/m ³
---	--

Rookgastemperatuur Flue gas temperature Température des fumees Abgastemperatur	209 °C
---	--------

Vermogen Thermal output Puissance Nennwärmeleistung	7.9 kW
--	--------

Rendement Energy efficiency Rendement Wirkungsgrad	≥ 75%
---	-------

Brandstoftypes Fuel types Types de carburant Zulassige Brennstoffe	Hout Wood Bois Holz
---	------------------------------

Gebruik alleen aanbevolen brandstoffen! Lees en volg de instructies!
Use only recommended fuels! Read and follow the operating instructions!
Utilisez un combustible approprié! Lire et suivre les notices d'instructions!
Brauch nur empfohlen Brennstoffe! Anleitung beachten!